



ROCKFAST[®] MODEL 620

- Engineered for the power and durability required for use with light gauge steel
- Sheet plastic collation prevents flagging
- Fingertip adjustable depth control to precisely place pin at desired depth
- Power to fasten to 12ga steel at the speed of nailing to wood
- Operates using typical jobsite air compressor at 120 psi maximum
- Full sequential actuation for accurate pin placement
- Capable of driving pins 1" to 2-1/2" long
- Systems approach with tools and fasteners provides single source responsibility



CONTACT & SERVICE

Our sales team
is available at:

T +43 7724 2111-671
sales.int@beck-fastening.com
www.beck-fastening.com

PIN TYPE

ASK-100 PINS, AKN-100 PINS, ADW-100 PINS

ROCKFAST® MODEL 620

TOOL CHARACTERISTICS

Height	Width	Length	Weight
12.56 inch	5.11 inch	11.02 inch	5.99 lbs
320 mm	130 mm	280 mm	2.68 kg

Pressure 70 - 120 psi | 5 - 8 bar
Lubricant Non-detergent pneumatic tool lubricant

Recommended steel thickness
22 ga - 12 ga



ROCKFAST® Model 620

FASTENER DATA

Pin Type	ASK-100-0100H	ADW-100	AKN-100-0100HA	AKN-100-0150HA	AKN-100-0200HA	AKN-100-0250HA
Wire	0.100" 2.50 mm					
Shank	Knurled					
Head	0.248" 6.3 mm					
Length	1" 25 mm	1 1/2" 38mm 2" 50 mm	1" 25 mm	1 1/2" 40 mm	2" 50 mm	2 1/2" 65 mm
Coating	Electro-galvanized		Aericoate® 1000			
Magazine Capacity	200 pins/coil					

ACTUATION & LOADING

Actuation System:
Full sequential actuation

Loading: Coil

AIR CONSUMPTION

@ 100 PSI

153.60 SLMP

Performance at 100 psi / 7 bar (0.7MPa)

KINETIC ENERGY

@ 100 PSI

62.82 joules | 46.33 ft-lfb

APPLICATIONS

- Face nailing HardiePanel® fiber cement siding to steel framing (ICC ES ESR-1844)
- Wood sheathing and wood structural panel diaphragms to steel framing (IAPMO ES ER-335)
- Interior drywall to steel studs 20ga and heavier
- Steel to steel fastening