



**TOOL-
FEATURES**

- Good balance
- High power for hardwood applications
- Rubber comfort grip ensures a non-slip handling and reduces vibration and fatigue
- Special nose for fence application
- Depth of drive adjustment

**FENCE
STAPLES**

- Patented Diamond Coating and precision divergent points for superior holding power compared to manual installation
- Hot dipped galvanized wire with minimum 350 g/m² (50 µm) zinc layer (Class 4) for maximum staple life
- RUS-Approval (ANSI C135.14)



CONTACT & SERVICE

Our sales team
is available at:


P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

The two divergent points and the patented Diamond Coating ensure an excellent holding power compared to manual installation.



**PRECISION
DIVERGENT
POINTS**



F46A FENCE 45-315

APPLICATIONS

- Fencing: batten fencing, electrified single wire, snow control fencing and light mesh fencing
- Pet enclosures, poultry fencing
- Coaxial and fiber optic utility wire applications

HANDLING

1. Load fastener from the top into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
323 mm	95 mm
12.72 inch	3.74 inch
Length	Weight
367 mm	3,35 kg
14.45 inch	7.38 lbs

Pressure

5 - 8 bar / 70 / 120 psi

Air consumption per shot

2.56 L. / 0.090 SCF

Performances at 90psi / 6.2 bar (0.62 MPa)

FASTENER DATA

	FENCE staples
Diameter	2,70 - 3,30 mm 0.106 - 0.130"
Outside Crown	12,80 mm 0.503"
Inside Crown	6,70 mm 0.264"
Length	25 - 45 mm 1 - 1 3/4"
Capacity	75
Staple Type	F45-315 FENCE staples

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 90.10 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 82.70 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System:
Single Shot

Loading: Top Loading

VARIATIONS

- F70G FENCE 45-315
FENCE Stapler

FASTENER PACKAGING:

Dimensions (WxHxD):
5.590x3.397x8.976"

Weight: 15.10 lbs (6,85 kg)

Quantity: 1500 pieces per pack

