

TOOL-**FEATURES**

- Powerful nailer for joist hanger nails and anchor nails
- Positive placement nose for metal connector plates
- Rubber comfort grip ensures a non-slip handling

ANCHOR AND JOIST HANGER NAILS

ANCHOR NAILS:

- High-performance resin for easy driving and increased pull-out force
- Hot dipped or electro galvanized
- with 12µm Special ring shaft for best with-drawal value

JOIST HANGER NAILS:

- Bright or electro-galvanized or hot dipped



CONTACT & SERVICE

DESCRIPTION

- Easy to handle thanks to its light weight and good balance
- Drives both joist hanger nails and anchor nails
- Fully pneumatic feeding and positioning system allows precise nailing



RAIMUND BECK NAGELTECHNIK GmbH

Raimund-Beck-Straße 1 | 5270 Mauerkirchen P +43 7724 2111-0 | F +43 7724 2111-20 E sales@beck-fastening.com W www.beck-fastening.com









F54 JOIST/ANCHOR 34-60

APPLICATIONS

- Metal connectors
- Roof joists
- · Rafters & joists
- Trusses

HANDLING

- 1. Load fastener from the top into the magazine
- 2. Connect air supply
- 3. Beware of recoil. Keep firm hold of the tool with both hands at all times
- 4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
350 mm	110 mm
13.78 inch	4.33 inch
Length	Weight
359 mm	2.74 kg
14.13 inch	604 lbs

Pressure

5.5 - 8 bar | 80 - 120 psi

Air consumption per shot

1.73 L. | 0.061 SCF Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA

Diameter	3.30 - 4.30 mm
	0.131 - 0.169"
Length	38 - 64 mm
	1 ½ - 2 ½"
Capacity	32
Nail Type	33° Joist Hanger
	Nails, Paper Tape
	& Plastic Strip
	33° Anchor Nails,
	Paper Tape &
	Plastic Strip

ACTUATION & LOADING

Actuation System: Single Shot

Loading: Rear Loading

VARIATIONS

• F70G JOIST/ANCHOR 34-60 (gas tool)

