



F58A CN15W-70

TOOL FEATURES

- Powerful Wire Coil Nailer
- Patent pending design with good ergonomics and excellent tool balance
- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue

15° WIRE COIL NAILS

- Can be provided in standard steel or stainless steel A2 or A4
- Available as bright, electro-galvanized, hot-dipped or coppered version
- Can be delivered in smooth, ring, screw or knurled version



CONTACT & SERVICE

Our sales team
is available at:

T +43 7724 2111-671
sales@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

- High impact engineered plastic magazine with adjustable bottom steel plate
- Body in high strength magnesium
- Magazine with adjustable bottom steel plate

APPLICATIONS

- Pallets
- Boxes & crates
- Cable reels
- Roof joists
- Rafters & joists
- Trusses

HANDLING

1. Load the coil in the magazine
2. Position first nail in nose channel and align top of nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry and dirty tool by cleaning and lubricating regularly

TOOL CHARACTERISTICS

Height	Width
318 mm	130 mm
12.52 inch	5.12 inch
Length	Weight
310 mm	3.45 kg
12.20 inch	7.61 lbs

Pressure

5 - 8 bar | 70 - 120 psi

Air consumption per shot

1.68 L. | 0.059 SCF
Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Diameter	2.30 - 2.90 mm 0.090 - 0.114"
Length	45 - 70 mm 1 ¾ - 2 ¾"
Head	7 mm 0.275"
Pitch	8 mm 0.315"
Nail Type	15° Wire Coil Nails
Capacity	200 300

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 99.57 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 90.56 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.34 m/s²

ACTUATION & LOADING

Actuation System:

Contact actuation

Loading: Coil

VARIATIONS

F58AC CN15W-80

