



**F58A CN15W-70**



### TOOL FEATURES

- Powerful Wire Coil Nailer
- Patent pending design with good ergonomics and excellent tool balance
- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue

### 15° WIRE COIL NAILS

- Can be provided in standard steel or stainless steel SS304 or SS316
- Available as bright, electro-galvanized, hot-dipped or coppered version
- Can be delivered in smooth, ring, screw or knurled version



### CONTACT & SERVICE

Our sales team  
is available at:

P +1 800 239 8665  
sales@beck-america.com  
www.beck-america.com

### DESCRIPTION

- High impact engineered plastic magazine with adjustable bottom steel plate
- Body in high strength magnesium
- Magazine with adjustable bottom steel plate

## APPLICATIONS

- Pallets
- Boxes & crates
- Cable reels
- Roof joists
- Rafters & joists
- Trusses

## HANDLING

1. Load the coil in the magazine
2. Position first nail in nose channel and align top of nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry and dirty tool by cleaning and lubricating regularly

## TOOL CHARACTERISTICS

Height	Width
318 mm	130 mm
12.52 inch	5.12 inch
Length	Weight
310 mm	3.45 kg
12.20 inch	7.61 lbs

### Pressure

5 - 8 bar | 70 - 120 psi

### Air consumption per shot

1.68 L. | 0.059 SCF

Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA

<b>Diameter</b>	2.30 - 2.90 mm 0.090 - 0.114"
<b>Length</b>	45 - 70 mm 1 ¾ - 2 ¾"
<b>Head</b>	7 mm   0.275"
<b>Pitch</b>	8 mm   0.315"
<b>Nail Type</b>	15° Wire Coil Nails
<b>Capacity</b>	200   300

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 99.57 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 90.56 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.34 m/s<sup>2</sup>

## ACTUATION & LOADING

Actuation System:

Contact actuation

Loading: Coil

## VARIATIONS

F58AC CN15W-80

