

TOOL-**FEATURES**

- Powerful cordless nailer for joist hanger nails and anchor nails
- Positive placement nose for metal connector plates
- Rubber comfort grip ensures a non-slip handling

ANCHOR AND JOIST HANGER NAILS

ANCHOR NAILS:

- High-performance resin for easy driving and increased pull-out force
- Hot dipped or electro galvanized
- with 12µm Special ring shaft for best with-drawal value

JOIST HANGER NAILS:

- Bright or electro-galvanized or hot dipped



CONTACT & SERVICE

DESCRIPTION

- Belt hook
- Single shot actuation
- Works with FASCO® fuel cells
- Powerful NiMh battery
- Lights indicate battery charge



Raimund-Beck-Straße 1 | 5270 Mauerkirchen P +43 7724 2111-0 | F +43 7724 2111-20 E sales@beck-fastening.com W www.beck-fastening.com









APPLICATIONS

- Metal connectors
- Roof joists
- · Rafters & joists
- Trusses

HANDLING

- 1. Load fuel cell
- 2. Load fastener from the rear into the magazine
- 3. Connect battery
- 4. Clean and maintain gas tool regularly

TOOL CHARACTERISTICS

Height	Width
393 mm	108 mm
15.47 inch	4.25 inch
Length	Weight
Length 360 mm	Weight 3.80 kg

Shot limit

1000 Shots / Hour

Speed

2-3 Shots / Second

Gas type Liquid petroleum gas

Operating temperature

-7 / 49° C | 19 / 120° F

FASTENER DATA

Diameter	3.30 - 4.30 mm 0.129 - 0.169"
Length	38 - 64 mm 1 ½ - 2 ½"
Capacity	32
Nail Type	33° Joist Hanger Nails, Paper Tape & Plastic Strip I 33° Anchor Nails,
	Paper Tape & Plastic Strip

ACTUATION & LOADING

Actuation System: Full Sequential Actuation

Loading: Rear Loading

VARIATIONS

• F54 JOIST/ANCHOR 34-60 (pneumatic tool)

BATTERY

Input Charge 220-240 VAC 50 Hz

Charge Time

2 hours

Capacity

1650 MaH

Voltage

6 VDC

Shots / Battery

Max. 5200

Shots / Fuel Cell

Max. 1200