

## SCRAIL® SPLITLESS

- Fine Thread SCRAIL® with a blunt "splitless" diamond point
- DIAMOND COATING for maximum holding power
- Optimized to work flawlessly in various wood species, e.g. soft wood like spruce and SYP
- Material: stainless steel
  A2 & A4, FasCoat®

# DIAMOND COATING

The expansion elements in the DIAMOND COATING diminish the friction between the fastener & the wood material. As a result of this reduced friction the fastener destroys less wood fibers, allowing more contact surface which results in increased withdrawal values.



## **CONTACT & SERVICE**

Our sales team is available at:

P +43 7724 2111-671 sales@beck-fastening.com www.beck-fastening.com

#### SPLITLESS DECKING WITH SCRAIL®

The SCRAIL® SPLITLESS was specially developed for fast installation of high-end decks. It has a blunt point to minimize the splitting of wood. For various requirements on corrosion protection, the SCRAIL® SPLITLESS is available in stainless steel or FasCoat®. For maximum holding power, the SCRAIL® SPLITLESS always comes with our patented DIAMOND COATING. Enjoy cordless decking in combination with the FASCO® F70G Cordless Strip Nailer.



**PATENTED** 



FASCO S.R.L. | A BECK COMPANY

Via Bruno Buozzi 2 40057 Cadriano di Granarolo Emilia | Bologna | ITALY P +39 051 60181 | F +39 051 766325 fasco@fasco-tools.com | www.fasco-tools.com









## **SCRAIL® SPLITLESS**

### **APPLICATION**

Decking with solid wood deck boards (optimized to work flawlessly in various wood species)



## **FASTENER DATA SCRAIL®**

	Stainless Steel SS304/A2	Stainless Steel SS316/A4	FasCoat®
Inner- & Outer diameter	2.8, 3.2 mm   2.9, 3.3 mm 0.113, 0.120"   0.116, 0.131"		
Drive Type	Torx <sup>®</sup> /Star		
Length	57 mm, 65 mm, 75 mm l 2 ¼", 2 ½", 3"		53 mm   2 1/8"
Capacity	200 - 300		
Collation Type	20° Plastic Strip SCRAIL® 33° Plastic Strip SCRAIL® 15° Plastic Sheet Coil SCRAIL®		

## COMPATIBLE FASCO® TOOLS

- F60A CN15W-PS90 SCR
- F70G RHN20-90 SCR (Cordless Strip Nailer)





