



## F1B 7C-16 STAPLER RANGE



### TOOL FEATURES

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- One hand latch for a faster reloading and reduced downtime
- Reversible bumper for high durability and increased parts life
- Bottom loading magazine speeds the reloading and keeps out the dirt

### FINE WIRE STAPLES

- Are useable in different surfaces and materials
- Are available in different materials
- Tip geometry suits the respective application

### FASCO<sup>®</sup> F1B 7C-16 TOOL RANGE:

- F1B 7C-16
- F1B 7C-16 LN50
- F1B 7C-16 AUT
- F1B 7C-16 AUT LM
- F1B 7C-16 LM
- F1B 7C-16 SAFETY C.T.

### DESCRIPTION

- Simple design, robust construction
- Easy maintenance
- Available in different variants and combinations like:  
**long magazine (LM), long nose (LN), contact safety (SAFETY C.T.) & automatic (AUT)**
- **WORLD-WIDE PATENTED ONE-TRIGGER-SYSTEM:** automatic design features a rapid valve controlled uniquely by the trigger itself. If the trigger is slightly depressed, the tool works in single shot system. By depressing the trigger fully, the tool switches over to the automatic firing sequence.

**RAIMUND BECK KG - Wire Staples Company**  
Raimund-Beck-Straße 1 | 5270 Mauerkirchen  
P +43 7724 2111-671  
E sales.int@beck-fastening.com  
W www.beck-fastening.com

# F1B 7C-16 STAPLER RANGE

## APPLICATIONS

- Upholstering
- Sofas
- Dust covers
- Insulation
- Furniture
- Case Backs
- Kitchen units
- Frame assembly
- Boat Interiors
- Trade Shows
- Picture Frames
- Carpets and underlay

## HANDLING

1. Load staples from the bottom into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## ACTUATION & LOADING

### ACTUATION SYSTEM:

#### F1B 7C-16 / LM / LN50 :

Single actuation

#### F1B 7C-16 CONTACT SAFETY:

Contact actuation

#### F1B 7C-16 AUT / AUT LM:

Continual actuation

### LOADING:

Bottom Loading

## FASTENER DATA

Outside Crown	9 mm   0.354"
Inside Crown	7,70 mm   0.303"
Diameter	0,60 x 0,75 mm   0.023 x 0.029"
Length	6 - 16 mm   ¼ - 5/8"
Magazine Capacity	180 (standard) 390 (long magazine)
Staple Type	BEA® 71, SENCO® C (=3G), BOSTITCH® 7, PREBENA V

## TOOL CHARACTERISTICS

TOOL	Height	Length	Width	Weight
F1B 7C-16	157 mm 6.18 inch	218 mm 8.58 inch	42 mm 1.65 inch	780 g 1.71 lbs
F1B 7C-16 LN50	205 mm 8.07 inch	218 mm 8.58 inch	42 mm 1.65 inch	825 g 1.82 lbs
F1B 7C-16 AUT	167 mm 6.57 inch	218 mm 8.58 inch	42 mm 1.65 inch	1070 g 2.36 lbs
F1B 7C-16 CONTACT SAFETY	162 mm 6.38 inch	218 mm 8.58 inch	42 mm 1.65 inch	880 g 1.94 lbs
F1B 7C-16 AUT LM	167 mm 6.57 inch	376 mm 14.80 inch	42 mm 1.65 inch	1370 g 3.00 lbs
F1B 7C-16 LM	157 mm 6.18 inch	376 mm 14.80 inch	42 mm 1.65 inch	1030 g 2.27 lbs

### Pressure

4 - 7 bar | 60 - 100 psi / 4,5 - 7 bar | 65 - 100 psi (CONTACT SAFETY) / 5 - 7 bar | 70 - 100 psi (AUT variations)

### Air consumption per shot

0.37 L. | 0.013 SCF Performance at 90 psi | 6.2 bar (0.62 MPa)

0.17 L. | 0.006 SCF Performance at 90 psi | 6.2 bar (0.62 MPa) (AUT variations)

## DIFFERENT VARIANTS AND COMBINATIONS LIKE



Changes and errors excepted. All rights reserved.

FASCO® is a registered trademark of the RAIMUND BECK KG.

BEA®, ATRO®, SENCO®, PREBENA® and BOSTITCH® are all trademarks of their respective owner.

**VERSION**  
**09/2022 EN**