



# TOOL FEATURES

- Nose specially designed for perfect hold of I-CLP clips
- 3 5 times faster than conventional installation
- Saves time and labour costs

#### INVISIDECK® SCRAIL®

- SCRAIL<sup>®</sup> nail screw fasteners (33° plastic strip) for use with the INVISIDECK<sup>®</sup> tool
- 2.8 / 3.2 x 38 mm
- Fine thread
- Phillips drive
- FASCOAT®
- Black

#### **CONTACT & SERVICE**

Our sales team is available at:

P +43 7724 2111-671 sales@beck-fastening.com www.beck-fastening.com

#### DESCRIPTION

Blind fastening systems are indispensable in modern decking installation. With the **INVISIDECK**<sup>®</sup> Hidden **SCRAIL**<sup>®</sup> system, decking can be installed with no visible or perceptible fasteners in a fifth of the time compared to traditional screw-fastening methods.





RAIMUND BECK NAGELTECHNIK GmbH Raimund-Beck-Straße 1 | 5270 Mauerkirchen P +43 7724 2111-0 | F +43 7724 2111-20 sales@beck-fastening.com www.beck-fastening.com



# F36 RHN33-38 DT INVISIDECK

#### **APPLICATIONS**

 Hidden fastening decking on metal or wood substructure



# TOOL CHARACTERISTICS

Height	Width
285 mm	114 mm
11.20 inch	4.48 inch
Length	Weight
326 mm	2.30 kg

**Pressure** 5,5 - 8 bar | 80 - 120 psi

Air consumption per shot 1.64 L. | 0.058 SCF Performance at 90 psi | 6.2 bar (0.62 MPa)

FASTENER DATA	
Diameter	3.20 mm 0.125"
Length	38 mm 1 ½"
Head	7 mm   0.275"
Nail Type	33° Plastic Strip SCRAIL® INVISIDECK®
Capacity	31
Clip	INVISIDECK® I-CLP, TC-G (TC-150)

#### HANDLING

- 1. Insert the clip into the decking board groove.
- 2. Fix the clip to the joist with a **SCRAIL**<sup>®</sup> nail screw fastener.
- 3. Place the next board on the clip.

Steps 1 and 2 are done in one step with the INVISIDECK<sup>®</sup> installation tool. (see pictures)

### **NOISE VALUE**

 $\begin{array}{l} ({\rm EN~12549}{+}{\rm A1}{\,:\,}2008,\,{\rm EN~ISO~4871}{\,:\,}2009) \\ {\rm L_{_{WA,1s}}:} 92.00 \ dB \ (A) - {\rm K_{_{WA,1s}}} \ , \ 2.5 \\ {\rm L_{_{pA,1s}}:} 105.00 \ dB \ (A) - {\rm K_{_{pA,1s}}} \ , \ 2.5 \end{array}$ 

## **VIBRATION VALUE**

(UNI ISO/TS 8662-11) 3.05 m/s<sup>2</sup>

## **ACTUATION & LOADING**

Actuation System: Single Shot Loading: Rear Loading

### INVISIDECK® I-CLP CLIP


Heavy gauge stainless steel clip for blind installation of grooved decking boards (25 mm or thicker).



### INVISIDECK® SLOT CUTTER

The **INVISIDECK**<sup>®</sup> slot cutter allows you to prepare decking boards optimally for further processing with the **INVISIDECK**<sup>®</sup> Hidden **SCRAIL**<sup>®</sup> system. Usable as well as wood composites and hardwoods without grooves.





# **VERSION** 11/2020 EN