



F44AC CN15W- PS65



TOOL FEATURES

- Switchable trigger for single shot and bump fire
- Tool-free depth of drive adjustment

15° WIRE COIL NAILS 15° PLASTIC SHEET COIL

- Can be provided in standard steel or stainless steel A2 or A4
- Available as bright, electro-galvanized, hot-dipped or coppered version
- Can be delivered in smooth, ring, screw or knurled version



CONTACT & SERVICE

Our sales team
is available at:

P +1 800 239 8665
sales.us@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

- Easy to handle thanks to its light weight and good balance
- Drives both wire welded and plastic sheet coil nails
- Fully pneumatic feeding and positioning system allows precise nailing
- Rubber comfort grip and adjustable exhaust
- Removable no mar tip

F44AC CN15W-PS65 SCR

APPLICATIONS

- Siding
- Fencing
- Subflooring
- Decking
- Roof joists
- Garden furniture
- Boxes and crates

HANDLING

1. Adjust magazine plate to nail length
2. Position first nail in nose channel and align top nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

| Height | Width |
|------------|-----------|
| 322 mm | 130 mm |
| 12.67 inch | 5.12 inch |
| Length | Weight |
| 275 mm | 2,40 kg |
| 10.82 inch | 5.29 lbs |

Pressure

5 - 8 bar | 70 - 120 psi

Air consumption per shot

1.20 L. | 0.042 SCF
Performance at 90 psi | 6.2 bar
(0.62 MPa)

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 92.02 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 81.50 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.47 m/s²

ACTUATION & LOADING

Actuation System: Single Shot
& Contact Actuation
Loading: Coil

VARIATIONS

F44AC CN15W-PS65 SCR

FASTENER DATA NAILS

| | Wire | Plastic |
|--------------------------|---|----------------------------|
| Diameter | 2.10 - 2.50 mm 0.083 - 0.099" | |
| Shank | smooth ring screw knurled | |
| Pitch | 7 - 8 mm 0.275 - 0.314" | 7.50 mm 0.295" |
| Head | 5 - 6 mm 0.197 - 0.236" | |
| Length | 25 - 65 mm 1 - 2 ½" | 32 - 65 mm 1 ¼ - 2 ½" |
| Magazine Capacity | 250 - 400 | 200 |
| Nail Type | 15° Wire Coil Nails 15° Plastic Sheet Coil Nails (CN-AG) | |

